

HIGH SPEED DOOR


SMOOTH R



Self Repair Function

TECHNICAL DATA

Opening Speed	1.4 / Sec. (Adjustable)
Closing speed	0.7 / Sec. (Adjustable)
DW min./max.	1,500 - 7,000 m.
DH min./max.	2,000 - 5,400 m.
Power supply	1p /3p /220 V/380V /20-25A/50Hz
Drive motor	Gear motor 0.75 - 2.2Kw. / IP 55
Controller systems	Inverter / IP65
Top Cover	Standard : Stainless Steel 304 Optional : Stainless Steel 201 Paint color coating
Side Frame	Standard : Stainless Steel 304 Optional : Stainless Steel 201 Paint color coating
Motor Cover	Standard : Stainless Steel 304 Optional : Stainless Steel 201 Paint color coating
Control Box	Standard : Stainless Steel 304 Optional : Stainless Steel 201 Paint color coating
Door curtain	PVC Curtain Thickness 0.9-1.2mm High -density polyester fabric
Zipper Type Track	Zipper inside the Track
Material	Plastic + Aluminum
Brush seal	Black Color
Wind load up to 700 Pa (Wind speed up to 100 km / h)	
Safety features	Electronic safety eage Photoeletronic safety sensor Airbag Safety System
Working temperature	-30 °C +70 °C



Control system : Mitsubishi Inverter
Mitsubishi PLC and other componentes
Dynamical system : SEW Germany Motor
0.75 / 1.5/ 2.2 KW, 220V/380V.



HIGH SPEED DOOR

SMOOTH R




SELF- REPAIR FUNCTION



Door Curtain


Fire Proof : LEVEL 2

1. Type of German Door Curtain
2. Thickness: 0.9-1.2mm
3. PVC Material
4. Maximum Resistant Cold Temperature: -40°C
5. With High-tech Nano technology Double-sided
6. Never contamination dust, bright as new
7. Dimension Size: Length: 1.5M, 50M / Per Coiling
8. Selected Color: Blue / Orange / Gray / Yellow



Transparent Curtain


1. Type of Transparent Door Curtain
2. Thickness: 1.5mm PVC Material
3. Dimension Size: Width: 0.7M, Length: Confirmed According to Customer's request.
4. Type of Transparent Door Curtain Feature:
 - Surface smooth and flawless
 - Good at Visual transparency
 - Manufacturing with New Technic and New Material



Zipper Type Track

Zipper inside the Track

Material : Plastic + Aluminum



Aluminum Track with Sealing Brushes

Interior Sealing Brushes

Better Performance than traditional Brushes



HIGH SPEED DOOR

SMOOTH A



Mitsubishi Inverter



Control Box



Main Shaft

Motor Main Shaft (Heat Treatmeant,
Excellent Wear Resistance Performance)



Round Plate

Laser Beam Cutting



HIGH SPEED DOOR

SMOOTH R



SELF- REPAIR FUNCTION



Big Beam Pipe

Thickness 2.5mm Material :
Steel with oil coating 6 Meters per Piece
Can be welded to any length



SEW Germany Motor

0.75 KW / 1.5 KW/ 2.2 KW



Head Cover & Motor Cover Frame

304 Stainless Steel



Photocell Sensor

For Door width <3.5m.,3.5-6.0 m



HIGH SPEED DOOR

SMOOTH R




SELF- REPAIR FUNCTION

CAN BE OPTIONAL



Safety edge sensor



Magnetic sensor

Inspect Metal ,
human body can not be inspected



Remote Control

One Set includes :
1 pcs receiver + 2 Remoters

Radar Sensor
Automatic Sensoring



HIGH SPEED DOOR

SMOOTH R



SELF- REPAIR FUNCTION

PVC CURTAIN

Specification

Polyester fiber and the surface coating processing

PVC CURTAIN

Thickness

0.9-1.2 mm.

PVC TRANSPARENT WINDOW

Thickness

0.9-1.5 mm.

